




34600 Solon Road • Solon, Ohio 44139-2695
 (440) 248-0100 • Fax: (440) 248-0723

24 Hour Response
 Chem Tel (1-800-255-3924)

MATERIAL SAFETY DATA SHEET

NFPA HAZARD RATING

- 4 EXTREME
- 3 HIGH
- 2 MODERATE
- 1 SLIGHT
- 0 INSIGNIFICANT



PAGE: 1 OF 3

PRODUCT NAME: CADWELD[®] MOLD SEALER (T403)

DATE PREPARED: 11/1/91

REVISED: 4/17/08

MSDS: 831H

I. INGREDIENTS

INGREDIENTS	CAS #	EXPOSURE LIMITS (mg/m ³)		WEIGHT RANGE	TSCA INV.
		OSHA PEL	ACGIH TLV		
KAOLIN	1332-58-7	TOTAL DUST 10.0 RESPIRABLE FRACTION 5.0	TOTAL DUST 10.0	NOT >15%	YES
WHEAT FLOUR	N/A	TOTAL DUST 15.0 RESPIRABLE FRACTION 5.0	TOTAL DUST 10.0 RESPIRABLE FRACTION 5.0	NOT >15%	
BENTONITE	1302-78-9	RESPIRABLE FRACTION 0.1 (VALUES APPLY TO RESPIRABLE QUARTZ ONLY, <2%)	RESPIRABLE FRACTION 0.1	NOT >20%	YES
SORBIC ACID	110-44-1	NOT AVAILABLE	NOT AVAILABLE	NOT >7%	YES
BORAX	1330-43-4	NOT AVAILABLE	NOT AVAILABLE	NOT >20%	YES
SODIUM CHLORIDE	7647-14-5	NOT AVAILABLE	NOT AVAILABLE	NOT >7%	YES
CARBOWAX	25322-68-3	NOT AVAILABLE	NOT AVAILABLE	NOT >10%	YES
SOYBEAN OIL	N/A	NOT AVAILABLE	NOT AVAILABLE	NOT >10%	

M A T E R I A L S A F E T Y D A T A S H E E T

ERICO, INC.

34600 Solon Road

Solon, Ohio 44139

(440) 248-0100

PAGE: 2 OF 3

PRODUCT NAME: CADWELD[®] MOLD SEALER

DATE PREPARED: 11/1/91

REVISED: 4/17/08

MSDS: 831H

2. PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N/A
VAPOR PRESSURE: N/A
VAPOR DENSITY: N/A
SOLUBILITY IN WATER: Slight
SPECIFIC GRAVITY (H₂O=1): 2.0
EVAPORATION RATE (Butyl Acetate = 1): N/A
V.O.C. = 0
MELTING POINT: N/A
APPEARANCE AND ODOR: Dough-like Texture

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): N/A
FLAMMABLE LIMITS: LEL - N/A UEL - N/A
EXTINGUISHING MEDIA: CO₂, Water, Foam, Sand
SPECIAL FIRE FIGHTING PROCEDURES: N/A
UNUSUAL FIRE AND EXPLOSION HAZARD: N/A

4. REACTIVITY DATA

STABILITY: Stable
CONDITIONS TO AVOID: None Known
INCOMPATIBILITY (MATERIALS TO AVOID): None Known
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: None
HAZARDOUS POLYMERIZATION: Will not occur.

5. HEALTH HAZARD DATA

ROUTES OF ENTRY: Primary route of entry - Inhalation of dry dust or smoke when heated.

HEALTH HAZARDS: Ingestion of material may cause gastrointestinal disturbances, including irritation, nausea, vomiting, and diarrhea.
If contact with skin produces irritation, wash affected area thoroughly with soap and water. A skin cream or lotion after washing may be helpful.

In the event of eye contact, flush the affected eye with water for at least 15 minutes. Do not rub eyes. Contact a physician if irritation persists.

M A T E R I A L S A F E T Y D A T A S H E E T

ERICO, INC.

34600 Solon Road

Solon, Ohio 44139

(440) 248-0100

PAGE: 3 OF 3

PRODUCT NAME: **CADWELD[®] MOLD SEALER**

DATE PREPARED: 11/1/91

REVISED: 4/17/08

MSDS: 831H

6. PRECAUTIONS FOR SAFE HANDLING AND USE

SPECIAL HANDLING AND STORAGE: Protect against water. Store in a cool, dry place. Keep in airtight container to prevent material from drying out.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

7. SPECIAL PROTECTION DATA

RESPIRATORY PROTECTION: Not required when used as directed.

PROTECTIVE GLOVES: Use recommended.

EYE PROTECTION: Safety glasses recommended.

VENTILATION: Material is generally used outdoors, therefore, no special ventilation is required.